

PRE-CON SPEC SHEET

Model: PC-30



Description: The PC30 Model pre-con is an Automatic suction valve designed to automatically adjust for the flow, keeping the prime in your hard-suction hose during drafting operations. The PC30 can also be used in hydrant operation when filling up your truck acting as a check valve to eliminate the need to close the valve after fill up when in the automatic position. This valve is compact, light-weight, durable and easy to maintenance/service. The PC30 comes with a pressure relief valve adjustable up to 250 PSI. The PC30 also comes with a 30 Degree down allowing a smooth connection and kink free hose operation. The PC30 comes with a 3-year manufactures warranty that is superior to its competition.

Material: A356 Aluminum, heat treated to a T-6 temper

Product Finish: Primer – Mil-Spec High Solids, VOC Compliant Epoxy polyamide primer with excellent chemical, solvent and corrosion resistance suitable to be used on aluminum. Top coat is a high solids aliphatic two component polyurethane coating.

GPM Flow Range: up to 1800 GPM (GPM may be restricted depending on set up and operation.) note: some friction loss may occur in operation due to the cone shape internal float.

Ideal Operation: Drafting and Hydrant Operation

Sizes Available: 4" NH, 4.5" NH, 5" NH, 6" NH

Weight of Product: 26 to 38 LBS (weight can vary depending on size and configuration)

Colors Available: Red